

B

C

E

公差表

| REV | ECN | LOCATIONS | DESCRIPTION | DATE       | CHANGER |
|-----|-----|-----------|-------------|------------|---------|
| A   |     |           | 新版本         | 2016-04-01 | 李国常     |

4

4

- SPECIFICATIONS
- Voltage rating: 200V AC, DC
- Current rating: 1A, AC, DC
- Withstanding Voltage: 500V AC/minute
- Insulation resistance: 100MΩ min
- Temperature range: -40℃~+85℃
- Contact resistance: 20MΩ max

■ HOUSING

- Part No: H1007-NP
- Poles: 08-30

TOLERANCE

0±0.30

.0±0.25

.00±0.20

.000±0.015

VER No SIZE

A A4

*KLETT*  
 深圳

成品规格图

|            |            |          |
|------------|------------|----------|
| TITLE      |            |          |
| CHECKED BY | DATE       | SCALE    |
| DRAWN BY   | UNIT:mm    | VER No   |
| 李国常        | 2016-04-01 | 1:1      |
|            | PART No    | H1007-NP |

B

C

D

E

F

B

C

E

公差表

| REV | ECN NO | LOCATIONS | DESCRIPTION | DATE       | CHANGER |
|-----|--------|-----------|-------------|------------|---------|
| A   |        |           | 新版本         | 2016-04-01 | 李国常     |

4

- SPECIFICATIONS
- Voltage rating: 50V AC, DC
  - Current rating: 1A, AC, DC
  - Withstanding Voltage: 500V AC/minute
  - Insulation resistance: 100MΩ min
  - Temperature range: -40°C~+85°C
  - Contact resistance: 20MΩ max

4

■ TERMINAL

- Part No: T1007PG
- Applicable wire: AWG#28-#32
- Material: Phosphor Bronze
- Finish: Gold-flash

B

C

D

E

F

**KLIT** 深圳市康利通电子科技有限公司

成品规格图

TOCERANCE

0±0.30

.0±0.25

.00±0.20

.000±0.015

VER No SIZE

A A4

TITLE

CHECKED BY

2016-04-01

SCALE

1:1


DRAWN BY

李国常

UNIT:mm

PART No

T1007PG



B

C

E

公差表

| REV | ECN NO | LOCATIONS | DESCRIPTION | DATE |
|-----|--------|-----------|-------------|------|
| A   |        |           |             |      |

■ WAFER

- Part No: W1007SR-NP
- Poles: 08, 14, 20, 30
- Material: Nylon 6T UL94V-0
- Ter Material: Phosphor Bronze /Gold-fla